

# SAFETY DATA SHEET

Revision Date 05/12/2015

## 1. PRODUCT AND COMPANY IDENTIFICATION

### 1.1 Product identifiers

Product name : Silica gel

Product Number : 80010

CAS-No. : 112926-00-8

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Manufacture of substances

### 1.3 Details of the supplier of the material on the safety data sheet

Company : Ladd Research  
83 Holly Court  
Williston, VT 05495  
USA

Telephone : 802-658-4961

Fax : 802-660-8859

### 1.4 Emergency telephone number

Emergency Phone # : +1-703-741-5500 (Chemtrec)

---

## 2. HAZARDS IDENTIFICATION

### 2.1 Classification of the substance or mixture

Not a hazardous substance or mixture.

### 2.2 GHS Label elements, including precautionary statements

Not a hazardous substance or mixture.

### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

---

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1 Substances

Formula : SiO<sub>2</sub>

CAS-No. : 112926-00-8

EC-No. : 231-545-4

#### Hazardous components

Component	Classification	Concentration
Silica-Amorphous, precipitated		<= 100 %

---

## 4. FIRST AID MEASURES

### 4.1 Description of first aid measures

#### General advice

Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration.

**In case of skin contact**

Wash off with soap and plenty of water.

**In case of eye contact**

Flush eyes with water as a precaution.

**If swallowed**

Never give anything by mouth to an unconscious person. Rinse mouth with water.

**4.2 Most important symptoms and effects, both acute and delayed**

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

**4.3 Indication of any immediate medical attention and special treatment needed**

No data available

---

**5. FIREFIGHTING MEASURES****5.1 Extinguishing media****Suitable extinguishing media**

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

**5.2 Special hazards arising from the substance or mixture**

No data available

**5.3 Advice for firefighters**

Wear self-contained breathing apparatus for firefighting if necessary.

**5.4 Further information**

No data available

---

**6. ACCIDENTAL RELEASE MEASURES****6.1 Personal precautions, protective equipment and emergency procedures**

Avoid dust formation. Avoid breathing vapours, mist or gas.

For personal protection see section 8.

**6.2 Environmental precautions**

No special environmental precautions required.

**6.3 Methods and materials for containment and cleaning up**

Sweep up and shovel. Keep in suitable, closed containers for disposal.

**6.4 Reference to other sections**

For disposal see section 13.

---

**7. HANDLING AND STORAGE****7.1 Precautions for safe handling**

Provide appropriate exhaust ventilation at places where dust is formed.

For precautions see section 2.2.

**7.2 Conditions for safe storage, including any incompatibilities**

Keep container tightly closed in a dry and well-ventilated place.

Moisture sensitive. Keep in a dry place.

**7.3 Specific end use(s)**

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

---

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION****8.1 Control parameters**

**Components with workplace control parameters**

Component	CAS-No.	Value	Control parameters	Basis
Silica-Amorphous, precipitated	112926-00-8	TWA	6 mg/m <sup>3</sup>	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
		TWA	20.000000Million particles per cubic foot	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
	Remarks	Millions of particles per cubic foot of air, based on impinger samples counted by light-field techniques. mppcf X 35.3 = million particles per cubic meter = particles per c.c		
		TWA	80.000000mg/m <sup>3</sup> / %SiO <sub>2</sub>	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
		See table Z-3		
		TWA	20.000000Million particles per cubic foot	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
		Millions of particles per cubic foot of air, based on impinger samples counted by light-field techniques. mppcf X 35.3 = million particles per cubic meter = particles per c.c		
		TWA	80.000000mg/m <sup>3</sup> / %SiO <sub>2</sub>	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
		TWA	20.000000Million particles per cubic foot	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
		Millions of particles per cubic foot of air, based on impinger samples counted by light-field techniques. mppcf X 35.3 = million particles per cubic meter = particles per c.c		
		TWA	80.000000mg/m <sup>3</sup> / %SiO <sub>2</sub>	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
		TWA	6.000000 mg/m <sup>3</sup>	USA. NIOSH Recommended Exposure Limits
		TWA	6.000000 mg/m <sup>3</sup>	USA. NIOSH Recommended Exposure Limits
		See table Z-3		
		TWA	20Million particles per cubic foot	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
		Millions of particles per cubic foot of air, based on impinger samples counted by light-field techniques. mppcf X 35.3 = million particles per cubic meter = particles per c.c		
		TWA	80mg/m <sup>3</sup> / %SiO <sub>2</sub>	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
		TWA	6 mg/m <sup>3</sup>	USA. NIOSH Recommended Exposure Limits

## 8.2 Exposure controls

### Appropriate engineering controls

General industrial hygiene practice.

### Personal protective equipment

#### Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: Nitrile rubber  
Minimum layer thickness: 0.11 mm  
Break through time: 480 min  
Material tested: Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact  
Material: Nitrile rubber  
Minimum layer thickness: 0.11 mm  
Break through time: 480 min  
Material tested: Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

### **Body Protection**

Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

### **Respiratory protection**

Respiratory protection is not required. Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN 143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

### **Control of environmental exposure**

No special environmental precautions required.

---

## **9. PHYSICAL AND CHEMICAL PROPERTIES**

### **9.1 Information on basic physical and chemical properties**

- |   |  |
|---|--|
| a) Appearance                                   | Form: powder<br>Colour: white                |
| b) Odour  | No data available                            |
| c) Odour Threshold                              | No data available                            |
| d) pH   | No data available                            |
| e) Melting point/freezing point                 | Melting point/range: > 1,600 °C (> 2,912 °F) |
| f) Initial boiling point and boiling range      | 2,230 °C (4,046 °F)                          |
| g) Flash point                                  | Not applicable                               |
| h) Evaporation rate                             | No data available                            |
| i) Flammability (solid, gas)                    | No data available                            |
| j) Upper/lower flammability or explosive limits | No data available                            |
| k) Vapour pressure                              | No data available                            |
| l) Vapour density                               | No data available                            |
| m) Relative density                             | No data available                            |
| n) Water solubility                             | No data available                            |
| o) Partition coefficient: n-octanol/water       | No data available                            |
| p) Auto-ignition                                | No data available                            |

temperature

q) Decomposition temperature No data available

r) Viscosity No data available

s) Explosive properties No data available

t) Oxidizing properties No data available

## 9.2 Other safety information

No data available

---

## 10. STABILITY AND REACTIVITY

### 10.1 Reactivity

No data available

### 10.2 Chemical stability

Stable under recommended storage conditions.

### 10.3 Possibility of hazardous reactions

No data available

### 10.4 Conditions to avoid

No data available

### 10.5 Incompatible materials

Strong oxidizing agents

### 10.6 Hazardous decomposition products

Other decomposition products - No data available  
In the event of fire: see section 5

---

## 11. TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects

#### Acute toxicity

No data available

Inhalation: No data available

Dermal: No data available

No data available

#### Skin corrosion/irritation

No data available

#### Serious eye damage/eye irritation

No data available

#### Respiratory or skin sensitisation

No data available

#### Germ cell mutagenicity

No data available

#### Carcinogenicity

IARC: 3 - Group 3: Not classifiable as to its carcinogenicity to humans (Silica-Amorphous, precipitated)

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a

carcinogen or potential carcinogen by OSHA.

**Reproductive toxicity**

No data available

No data available

**Specific target organ toxicity - single exposure**

No data available

**Specific target organ toxicity - repeated exposure**

No data available

**Aspiration hazard**

No data available

**Additional Information**

RTECS: VV7315000

Amorphous silica is not classifiable as to its carcinogenicity to humans (Group 3); however, crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (Group 1, IARC). Therefore, amorphous silica should be handled as if possessing the same hazards as the crystalline form., To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Stomach - Irregularities - Based on Human Evidence

Stomach - Irregularities - Based on Human Evidence

---

**12. ECOLOGICAL INFORMATION**

**12.1 Toxicity**

No data available

**12.2 Persistence and degradability**

No data available

**12.3 Bioaccumulative potential**

No data available

**12.4 Mobility in soil**

No data available

**12.5 Results of PBT and vPvB assessment**

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

**12.6 Other adverse effects**

No data available

---

**13. DISPOSAL CONSIDERATIONS**

**13.1 Waste treatment methods**

**Product**

Offer surplus and non-recyclable solutions to a licensed disposal company.

**Contaminated packaging**

Dispose of as unused product.

---

**14. TRANSPORT INFORMATION**

**DOT (US)**

Not dangerous goods

**IMDG**

Not dangerous goods

**IATA**

Not dangerous goods

---

**15. REGULATORY INFORMATION****SARA 302 Components**

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313 Components**

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**SARA 311/312 Hazards**

Chronic Health Hazard

**Massachusetts Right To Know Components**

	CAS-No.	Revision Date
Silica-Amorphous, precipitated	112926-00-8	1993-04-24

**Pennsylvania Right To Know Components**

	CAS-No.	Revision Date
Silica-Amorphous, precipitated	112926-00-8	1993-04-24

**New Jersey Right To Know Components**

	CAS-No.	Revision Date
Silica-Amorphous, precipitated	112926-00-8	1993-04-24

**California Prop. 65 Components**

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

---

**16. OTHER INFORMATION****HMIS Rating**

Health hazard:	0
Chronic Health Hazard:	*
Flammability:	0
Physical Hazard	0

**NFPA Rating**

Health hazard:	0
Fire Hazard:	0
Reactivity Hazard:	0

**Disclaimer**

The information presented is believed to be correct and is the most accurate information available to us at this time. However, Ladd Research makes no warranty, express or implied, and assumes no liability for this information and the product described herein.

Date Prepared: 05/12/2015