

Distributed By: Ladd Research
 3 Ewing Place
 Essex Junction, VT 05452
 Tel: (802) 658-4961
 Fax: (802) 660-8859
 email: sales@laddresearch.com
 Web: www.laddresearch.com



Issue date: 05/04/2023

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:	SB-10	IDH number:	1224914
Product type:	Paints and coatings	Region:	United States
Restriction of Use:	None identified	Contact information:	
Company address:			
Henkel Electronic Materials LLC	Telephone: +1 (888) 943-6535		
14000 Jamboree Road	MEDICAL EMERGENCY Phone: Poison Control Center		
Irvine, CA 92606	1-877-671-4608 (toll free) or 1-303-592-1711		
	TRANSPORT EMERGENCY Phone: CHEMTREC		
	1-800-424-9300 (toll free) or 1-703-527-3887		
	Internet: www.henkel.com/electronics		

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: HIGHLY FLAMMABLE LIQUID AND VAPOR.
 MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.
 CAUSES SKIN IRRITATION.
 MAY CAUSE AN ALLERGIC SKIN REACTION.
 CAUSES SERIOUS EYE IRRITATION.
 MAY CAUSE DROWSINESS OR DIZZINESS.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	2
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3
ASPIRATION HAZARD	1

PICTOGRAM(S)



Precautionary Statements

Prevention:	Keep away from heat, sparks, open flames, hot surfaces - no smoking. Keep container tightly closed. No release into water. Use explosion-proof equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing vapors, mist, or spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, and face protection.
Response:	IF SWALLOWED: Immediately call a physician or poison control center. If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison control center or physician if you feel unwell. Do NOT induce vomiting. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing. In case of fire: Use foam, dry chemical or carbon dioxide to extinguish.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Propyl acetate	109-60-4	30 - 60
Hydroxy-2-methylpentan-4-on-2	123-42-2	30 - 60
2-Propanol	67-63-0	10 - 30
n-Butyl alcohol	71-36-3	1 - 5

* Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: If inhaled, immediately remove the affected person to fresh air. If symptoms develop and persist, get medical attention.

Skin contact: Remove contaminated clothing and footwear. Immediately wash skin thoroughly with soap and water. If symptoms develop and persist, get medical attention.

Eye contact: In case of contact with the eyes, rinse immediately with plenty of water for 15 minutes, and seek immediate medical attention.

Ingestion: Get immediate medical attention. DO NOT induce vomiting unless directed to do so by medical personnel. Drink 1 or 2 glasses of water. Never give anything by mouth to a victim who is unconscious or is having convulsions.

Symptoms: See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear full protective clothing. Wear self-contained breathing apparatus.

Unusual fire or explosion hazards: DANGEROUS when exposed to heat or flame. This material can be ignited by flame or spark under all normal atmospheric conditions. Vapors are heavier than air and may travel to ignition sources and flash back.

Hazardous combustion products: Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Prevent further leakage or spillage if safe to do so. Remove all sources of ignition. Wear appropriate protective equipment and clothing during clean-up.

Clean-up methods:

Collect spilled material with an inert absorbent such as sand or vermiculite. Place in properly labeled closed container. Dispose of according to Federal, State and local governmental regulations.

7. HANDLING AND STORAGE

Handling:

Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Avoid breathing vapors or mists of this product. Do not take internally. For industrial use only. Keep away from heat, spark and flame.

Storage:

For safe storage, store between 5.0 °C (41°F) and 30.0 °C (86°F). Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Remove all sources of ignition. Ground and bond metal containers for liquid transfer to avoid static sparks.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Propyl acetate	200 ppm TWA 250 ppm STEL	200 ppm (840 mg/m3) PEL	None	None
Hydroxy-2-methylpentan-4-on-2	50 ppm TWA	50 ppm (240 mg/m3) PEL	None	None
2-Propanol	200 ppm TWA 400 ppm STEL	400 ppm (980 mg/m3) PEL	None	None
n-Butyl alcohol	20 ppm TWA	100 ppm (300 mg/m3) PEL	None	None

Engineering controls:

Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product. Explosion-proof exhaust devices are required.

Respiratory protection:

If ventilation is not sufficient to effectively prevent buildup of aerosols, mists or vapors, appropriate NIOSH/MSHA respiratory protection must be provided.

Eye/face protection:

Wear chemical goggles; face shield (if splashing is possible).

Skin protection:

Wear impervious gloves for prolonged contact. Gloves should be tested to determine suitability for prolonged contact. Use of impervious apron and boots are recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Color:	Colorless
Odor:	Strong, sweet
Odor threshold:	Not available.
pH:	Not applicable
Vapor pressure:	22 mm hg
Boiling point/range:	> 82 °C (> 179.6 °F) None
Melting point/ range:	< -43 °C (< -45.4 °F) calculated
Specific gravity:	0.86
Vapor density:	> 2 (Air = 1)
Flash point:	11.6 °C (52.88 °F) Closed cup
Flammable/Explosive limits - lower:	1.5 %
Flammable/Explosive limits - upper:	10 %
Autoignition temperature:	> 343 °C (> 649.4 °F)
Evaporation rate:	Not determined
Solubility in water:	Appreciable
Partition coefficient (n-octanol/water):	Not determined

VOC content: 860 g/l
 Viscosity: < 1,000 cp
 Decomposition temperature: Not available.

10. STABILITY AND REACTIVITY

Stability: Stable at normal conditions.

Hazardous reactions: Will not occur.

Hazardous decomposition products: Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

Incompatible materials: This product may react with oxidizing agents.

Reactivity: Not available.

Conditions to avoid: Keep away from heat, spark and flame.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects/Symptoms

Inhalation: This product is irritating to the respiratory system. Excessive inhalation of this material causes headache, dizziness, nausea and incoordination.

Skin contact: May cause mild skin irritation. A component in this product may be absorbed through the skin in harmful amounts.

Eye contact: This product is severely irritating to the eyes and may cause irreversible damage including burns and blindness.

Ingestion: Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Propyl acetate	Oral LD50 (RABBIT) = 6.64 g/kg Oral LD50 (RAT) = 9,370 mg/kg	Central nervous system, Irritant
Hydroxy-2-methylpentan-4-on-2	Oral LD50 (RAT) = 4.0 g/kg	Blood, Central nervous system, Irritant, Kidney, Liver
2-Propanol	Oral LD50 (RAT) = 5,045 mg/kg Oral LD50 (RABBIT) = 6,410 mg/kg Oral LD50 (RAT) = 4.7 g/kg Oral LD50 (RABBIT) = 8.0 g/kg Oral LD50 (RABBIT) = 5.03 g/kg Dermal LD50 (RABBIT) = 12,800 mg/kg	Allergen, Blood, Brain, Central nervous system, Irritant, Kidney, Liver, Spleen
n-Butyl alcohol	Oral LD50 (RAT) = 790 mg/kg Dermal LD50 (RABBIT) = 3,400 mg/kg Inhalation LC50 (RAT, 4 h) = 8000 ppm	Allergen, Central nervous system, Ear, Eyes, Irritant

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Propyl acetate	No	No	No
Hydroxy-2-methylpentan-4-on-2	No	No	No
2-Propanol	No	No	No
n-Butyl alcohol	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Harmful to aquatic organisms.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: If discarded, this product is considered a RCRA ignitable waste, D001. This product contains a component or components identified as hazardous under 40 CFR 261.24. U031

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Paint related material
Hazard class or division: 3
Identification number: UN 1263
Packing group: II

International Air Transportation (ICAO/IATA)

Proper shipping name: Paint related material
Hazard class or division: 3
Identification number: UN 1263
Packing group: II

Water Transportation (IMO/IMDG)

Proper shipping name: PAINT RELATED MATERIAL
Hazard class or division: 3
Identification number: UN 1263
Packing group: II

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis
CERCLA/SARA Section 311/312: Immediate Health, Fire
CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). n-Butyl alcohol (CAS# 71-36-3).

California Proposition 65: No California Proposition 65 listed chemicals are known to be present.

Canada Regulatory Information

CEPA DSL/NDL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Issue date: 05/04/2023

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.