Distributed By: Ladd Research

3 Ewing Place

Essex Junction, VT 05452 Tel: (802) 658-4961 Fax: (802) 660-8859

email: sales@laddresearch.com Web: www.laddresearch.com

# **Safety Data Sheet**



Issue date: 05/04/2023

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: BONDERITE L-GP GP460 AERO AN

known as ACHESONGP460

Product type: Lubricant
Restriction of Use: None identified

Company address: Henkel Corporation One Henkel Way

Rocky Hill, Connecticut 06067

**IDH number:** 1225096

Item number:1225096Region:United States

Contact information: Telephone: (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

## 2. HAZARDS IDENTIFICATION

WARNING: CAUSES SKIN IRRITATION.
CAUSES SERIOUS EYE IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A

#### PICTOGRAM(S)



#### **Precautionary Statements**

**Prevention:** Wash thoroughly after handling. Wear eye and face protection. Wear protective gloves. **Response:** IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for

several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical attention. Take

off contaminated clothing.

Storage: Not prescribed Disposal: Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

### See Section 11 for additional toxicological information.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Graphite	7782-42-5	30 - 60
Petrolatum	8009-03-8	30 - 60
White mineral oil (petroleum), highly refined	8042-47-5	5 - 10

IDH number: 1225096 Product name: BONDERITE L-GP GP460 AERO AN known as ACHESONGP460 Page 1 of 6

#### 4. FIRST AID MEASURES

Inhalation: If inhaled, immediately remove the affected person to fresh air. If symptoms

develop and persist, get medical attention.

Skin contact: Immediately wash skin thoroughly with soap and water. If symptoms develop

and persist, get medical attention.

Eye contact: In case of contact with the eyes, rinse immediately with plenty of water for 15

minutes, and seek immediate medical attention.

Ingestion: Get medical attention. Do not induce vomiting. Never give anything by mouth

to a victim who is unconscious or is having convulsions.

Symptoms: See Section 11.

IDH number: 1225096

#### 5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear full protective clothing. Wear self-contained breathing apparatus.

Unusual fire or explosion hazards: May liberate large quantities of dense, foul-smelling smoke which may contain

unidentified toxic gasses. Formation of toxic gases is possible during heating

or in fires.

Hazardous combustion products: Upon decomposition, this product emits carbon monoxide, carbon dioxide

and/or low molecular weight hydrocarbons.

### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Prevent further leakage or spillage if safe to do so. Wear appropriate

protective equipment and clothing during clean-up. Do not allow product to

enter sewer or waterways.

Clean-up methods: Absorb spill with inert material. Shovel material into appropriate container for

disposal. Dispose of according to Federal, State and local governmental

regulations.

### 7. HANDLING AND STORAGE

**Handling:** Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

Keep away from heat, spark and flame. Avoid breathing vapors or mists of this

product. For industrial use only.

Storage: For safe storage, store between 5.0 °C (41°F) and 30.0 °C (86°F)

Keep container tightly closed and in a cool, well-ventilated place away from

incompatible materials. Keep out of direct sunlight.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

<sup>\*</sup> Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Graphite	2 mg/m3 TWA Respirable fraction.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. 15 MPPCF TWA	None	None
Petrolatum	5 mg/m3 TWA Inhalable fraction. Exposure by all routes should be carefully controlled to levels as low as possible. Included in the regulation but with no data values. See regulation for further details	5 mg/m3 PEL Mist.	None	None
White mineral oil (petroleum), highly refined	5 mg/m3 TWA Inhalable fraction.	5 mg/m3 TWA mist 5 mg/m3 PEL Mist.	None	None

Engineering controls: Provide local and general exhaust ventilation to effectively remove and

prevent buildup of any vapors or mists generated from the handling of this

product.

Respiratory protection: If ventilation is not sufficient to effectively prevent buildup of aerosols, mists or

vapors, appropriate NIOSH/MSHA respiratory protection must be provided.

**Eye/face protection:** Wear chemical goggles; face shield (if splashing is possible).

**Skin protection:** Wear impervious gloves for prolonged contact. Use of impervious apron and

boots are recommended.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid Color: Gray Odor: Slight Odor threshold: Not available. pH: Not applicable Vapor pressure: < 1 mm hg calculated 300 °C (572°F) Boiling point/range: Melting point/ range: 0 °C (32°F)

Specific gravity: 1.199

Vapor density: Not applicable

Flash point: 200 °C (392°F) Pensky Martens closed cup

Flammable/Explosive limits - lower:

Flammable/Explosive limits - upper:

Autoignition temperature:

Evaporation rate:

Solubility in water:

Partition coefficient (n-octanol/water):

VOC content:

Not available.

Not applicable

Negligible

Not available.

O g/l

VOC content: 0 g/l
Viscosity: Not available.

Decomposition temperature: Not available.

IDH number: 1225096

# 10. STABILITY AND REACTIVITY

Stability: Stable at normal conditions.

Hazardous reactions: Will not occur.

Hazardous decomposition

products:

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low

molecular weight hydrocarbons.

**Incompatible materials:** This product may react with strong oxidizing agents.

Reactivity: Not available.

Conditions to avoid: Keep away from heat, ignition sources and incompatible materials. High temperatures.

## 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

#### Potential Health Effects/Symptoms

IDH number: 1225096

Inhalation: This product is irritating to the respiratory system. Excessive inhalation of this material causes

headache, dizziness, nausea and incoordination.

Skin contact: This product is irritating to the skin. Symptoms may include redness, edema, drying, defatting

and cracking of the skin.

**Eye contact:** This product is irritating to the eyes.

Ingestion: May cause gastrointestinal tract irritation if swallowed. May cause dizziness, incoordination,

headache, nausea, and vomiting.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Graphite	None	Lung
Petrolatum	None	Irritant
White mineral oil (petroleum), highly refined	None	Irritant

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Graphite	No	No	No
Petrolatum	No	No	No
White mineral oil (petroleum), highly refined	No	No	No

## 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

**Hazardous waste number:**Material, if discarded, is not expected to be a characteristic hazardous waste

under RCRA.

### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

### 15. REGULATORY INFORMATION

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis

CERCLA/SARA Section 311/312: Immediate Health

CERCLA/SARA Section 313: None above reporting de minimis

California Proposition 65: No California Proposition 65 listed chemicals are known to be present.

**Canada Regulatory Information** 

IDH number: 1225096

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

#### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

**Issue date:** 05/04/2023

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

IDH number: 1225096